

# SAFETY DATA SHEET

Issuing Date 10-Nov-2015

Revision Date 10-Nov-2015

Revision Number 1

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product identifier

Product Name S-9300 Bond-Kote Gray

### Other means of identification

Synonyms None

### Recommended use of the chemical and restrictions on use

Recommended Use Industrial Use Only

Uses advised against No information available

### Details of the supplier of the safety data sheet

Supplier Name Arizona Polymer Flooring, Inc.

Supplier Address 4565 W. WATKINS ST.  
PHOENIX, AZ 85043  
US

Supplier Phone Number Phone:623-435-2277

Supplier Website www.super-krete.com

### Emergency telephone number

Company Emergency Phone Number 800-424-9300

## 2. HAZARDS IDENTIFICATION


### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Carcinogen	Category 1A
Specific Target Organ Toxicity (STOT) following repeated exposures	Category 1
Eye Damage/Eye Irritation	Category 1
Skin Irritant	Category 2

**GHS Label elements, including precautionary statements:** Carcinogen

## Emergency Overview

<b>Signal word</b>	<b>Warning</b>
<b>Hazard Statements</b> May cause cancer by inhalation. Causes damage to lungs, kidneys and autoimmune system through prolonged or repeated exposure by inhalation. Causes skin irritation and serious eye irritation. May cause an allergic skin reaction. May cause respiratory irritation.	
	
<b>Appearance</b> Gray	<b>Physical state</b> Solid/Powder Solid
	<b>Odor</b> None

**Precautionary Statements - Prevention**

Do not handle until the safety information presented in this SDS has been read and understood.  
 Do not eat, drink or smoke while manually handling this product.  
 Wash face, hands and any exposed skin thoroughly after handling.  
 Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray.  
 Avoid creating dust when handling, using or storing.  
 Use with adequate ventilation to keep exposure below recommended exposure limits.  
 Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area.  
 Wear eye and respiratory protection following this SDS, NIOSH guidelines and other applicable regulations.

**Precautionary Statements - Response**

Specific treatment (see supplemental first aid instructions on this label)

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention

**Skin**

IF ON SKIN: Wash with plenty of soap and water  
 Take off contaminated clothing and wash before reuse  
 If skin irritation or rash occurs: Get medical advice/attention

**Ingestion**

IF SWALLOWED: Rinse mouth and do not induce vomiting.

**Inhalation**

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor/physician if you feel unwell

If exposed, concerned, unwell or irritation of the eyes, skin, mouth or throat/nasal passage persist: Get medical attention.

#### **Precautionary Statements - Storage**

Keep stored off the ground and away from walls in a cool, dry, well ventilated area. Do not allow exposure to moisture or water. Store in a tightly closed container.

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant. Dispose of the product in accordance with local, regional, national or international regulations.

#### **Hazards not otherwise classified (HNOC)**

Not applicable

#### **Unknown Toxicity**

100% of the mixture consists of ingredient(s) of unknown toxicity

#### **Other information**

Repeated or prolonged skin contact may cause allergic reactions with susceptible persons

#### **Interactions with Other Chemicals**

No information available.

### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

<b>Chemical Name</b>	<b>CAS No</b>	<b>Weight-%</b>	<b>Trade Secret</b>
Supplier Trade Secret	Proprietary	30 - 60	*
Supplier Trade Secret	Proprietary	15 - 40	*
Supplier Trade Secret	Proprietary	10 - 30	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret

### **4. FIRST AID MEASURES**

#### **First aid measures**

##### **General Advice**

Show this safety data sheet to the doctor in attendance.

##### **Eye contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Do not rub affected area.

##### **Skin contact**

Wash off immediately with soap and plenty of water for at least 15 minutes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.

##### **Inhalation**

Remove to fresh air. Get medical attention immediately if symptoms occur.

##### **Ingestion**

Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.

**Self-protection of the first aider** Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8).

**Most important symptoms and effects, both acute and delayed**

**Most Important Symptoms and Effects** Burning sensation. Itching. Rashes. Hives. Coughing and/ or wheezing.

**Indication of any immediate medical attention and special treatment needed**

**Notes to Physician** May cause sensitization of susceptible persons. Treat symptomatically.

## **5. FIRE-FIGHTING MEASURES**

**Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media**

CAUTION: Use of water spray when fighting fire may be inefficient.

**Specific hazards arising from the chemical**

Product is or contains a sensitizer. May cause sensitization by skin contact.

**Uniform Fire Code** Sensitizer: Solid

**Hazardous Combustion Products**

Carbon oxides.

**Explosion Data**

**Sensitivity to Mechanical Impact** No.

**Sensitivity to Static Discharge** No.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, OSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas.

**Other Information** Refer to protective measures listed in Sections 7 and 8.

### Environmental precautions

**Environmental precautions** Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so.

### Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up and transfer to properly labeled containers.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children.

**Incompatible Products** Strong acids. Strong oxidizing agents. Strong bases.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Supplier Trade Secret	TWA: 0.025 mg/m <sup>3</sup> respirable fraction	TWA: 0.1 mg/m <sup>3</sup> (vacated)	IDLH: 50 mg/m <sup>3</sup> respirable dust TWA: 0.05 mg/m <sup>3</sup> respirable dust
Supplier Trade Secret	TWA: 1 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction TWA: 50 mppcf <1% Crystalline silica	IDLH: 5000 mg/m <sup>3</sup> TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

### Appropriate engineering controls

**Engineering Measures**

- Showers
- Eyewash stations
- Ventilation systems

### Individual protection measures, such as personal protective equipment

**Engineering Controls** Ventilation: Use local exhaust, general ventilation or natural ventilation adequate to maintain exposures below appropriate exposure limits.

**Other control measures** Respirable dust and crystalline silica levels should be monitored regularly. Dust levels in excess of appropriate exposure limits should be reduced by implementing feasible engineering controls, including (but not limited to) dust suppression (wetting), ventilation, process enclosure and enclosed employee work stations.

**Eye/Face Protection** Safety glasses with side shields should be worn as minimum protection. Dust goggles should be worn when excessively (visible) dusty conditions are present or are anticipated. If irritation persists, get medical attention immediately. There is potential for severe eye irritation if exposed to excessive concentrations of dust for those using contact lenses.

**Skin Protection** Chemical resistant apron. Loose clothing, with the neck closed and sleeves rolled down. Safety shoes should be laced so that no openings are left through which concrete may reach the skin. Use appropriate chemical resistant protective gloves if manually handling the product.

**General Hygiene Considerations** There are no known hazards associated with this material when used as recommended. Following the guidelines in this SDS are recognized as good industrial hygiene practices. Avoid breathing dust. Avoid skin and eye contact. Wash dust-exposed skin with soap and water before eating, drinking, smoking and using toilet facilities. Wash work clothes after each use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Physical and Chemical Properties

<b>Physical state</b>	Solid/Powder, Solid	<b>Odor</b>	None
<b>Appearance</b>	Gray	<b>Odor Threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH	No data available	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	No data available	None known	
Flash Point	No data available	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air			
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor pressure	No data available	None known	
Vapor density	No data available	None known	
Specific Gravity	No data available	None known	
Water Solubility	Slightly soluble	None known	
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octanol/water	No data available	None known	
Autoignition temperature	No data available	None known	
Decomposition temperature	No data available	None known	
Kinematic viscosity	No data available	None known	
Dynamic viscosity	No data available	None known	
Explosive properties	No data available		
Oxidizing properties	No data available		

### Other Information

<b>Softening Point</b>	No data available
<b>VOC Content (%)</b>	No data available
<b>Particle Size</b>	No data available
<b>Particle Size Distribution</b>	

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available.

### Chemical stability

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

None under normal processing.

### Hazardous Polymerization

Hazardous polymerization does not occur.

### Conditions to avoid

None known based on information supplied.

### Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

### Hazardous Decomposition Products

Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

**Health Effects:** The information below represents an overview of health effects caused by overexposure to one or more components in Portland cement.

<b>Inhalation</b>	Dust may irritate nose, throat, mucous membranes and respiratory tract by mechanical abrasion. Coughing, sneezing, chest pain, shortness of breath, inflammation of mucous membrane, and flu-like fever may occur following exposures in excess of appropriate exposure limits.
<b>Eye contact</b>	Direct contact with dust may cause irritation by mechanical abrasion or corrosive action. Conjunctivitis may occur.
<b>Skin contact</b>	Direct contact may cause irritation by mechanical abrasion. Some components of material are also known to cause corrosive effects to skin and mucous membranes.
<b>Skin Absorption</b>	Not expected to be a significant route of exposure.
<b>Ingestion</b>	Small amounts (a tablespoonful) swallowed during normal handling operations are not likely to cause injury. Ingestion of large amounts may cause gastrointestinal irritation and blockage.
<b>Medical Conditions Aggravated by Exposure:</b>	Inhaling respirable dust may aggravate existing respiratory system disease(s) (e.g., bronchitis, emphysema, chronic obstructive pulmonary disease) and/or dysfunctions. Exposure to dust may aggravate existing skin and/or eye conditions. Smoking and obstructive/restrictive lung diseases may also exacerbate the effects of excessive exposure to this product. This product is a mixture of components including Portland Cement.
<b>Portland Cement: Exposure Routes:</b>	Inhalation, ingestion, skin and/or eye contact
<b>Target Organs:</b>	Eyes, skin, respiratory system.



**Acute Effect:** Exposure to dry portland cement may cause drying of the skin and mild irritation, or more significant effects from the aggravation of other conditions. Eye exposures to portland cement may cause immediate or delayed irritation or inflammation of the cornea. Eye contact with larger amounts of dry powder or splashes of liquid portland cement may cause effects ranging from moderate eye irritation to chemical burns and blindness. Inhalation of dry portland cement may cause irritation to the moist mucous membranes of the nose, throat and upper respiratory system, or may cause or aggravate certain lung diseases or conditions.

**Chronic Effect:** Prolonged exposure can cause severe skin damage in the form of chemical (caustic) burns. Portland Cement is not listed as carcinogen on the NTP, IARC or OSHA list of carcinogens, however Portland Cement contains trace amounts of hexavalent chromium [Cr(VI)] and certain chromium compounds which are listed on the NTP and IARC lists of carcinogens. The total amounts of chromium and chromium compounds in Portland Cement are typically less than 0.003% and hexavalent chromium less than 0.001%. Note: Some individuals who are exposed to portland cement may exhibit an allergic response, which can result in symptoms ranging from mild rashes to severe skin ulcers. Cement dermatitis may be irritant contact dermatitis induced by the alkaline or it may be allergic contact dermatitis elicited by an immunological reaction to Cr(VI), or it may be a combination of the two.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** May cause sensitization of susceptible persons. May cause sensitization by skin contact.

**Mutagenic Effects** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Supplier Trade Secret			Known	X

*NTP (National Toxicology Program)*

*Known - Known Carcinogen*

*OSHA (Occupational Safety and Health Administration of the US Department of Labor)*

*X - Present*

**California Proposition 65** Crystalline silica in October 1996 was listed on the Safe Drinking Water and Toxic Enforcement ACT of 1986 as a chemical known to the state to cause cancer or reproductive toxicity.

**Reproductive toxicity** No information available.

**STOT - single exposure** Respiratory system.

**STOT - repeated exposure** Specific Target Organ Toxicity.

**Chronic Toxicity** No known effect based on information supplied. Contains a known or suspected carcinogen.

**Target Organ Effects** Respiratory system. Eyes. Skin.

**Aspiration Hazard** No information available.

**Numerical measures of toxicity Product Information**

The following values are calculated based on chapter 3.1 of the GHS document  
Not applicable

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

The environmental impact of this product has not been fully investigated.

### Persistence and Degradability

No information available.

### Bioaccumulation

No information available

### Other adverse effects

No information available.

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

#### **Disposal methods**

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

#### **Contaminated Packaging**

Dispose of contents/containers in accordance with local regulations.

## 14. TRANSPORT INFORMATION

<u>DOT</u>	NOT REGULATED
Proper Shipping Name	NON REGULATED
Hazard Class	N/A
<u>TDG</u>	Not regulated
<u>MEX</u>	Not regulated
<u>ICAO</u>	Not regulated
<u>IATA</u>	Not regulated
Proper Shipping Name	NON REGULATED
Hazard Class	N/A
<u>IMDG/IMO</u>	Not regulated
Hazard Class	N/A

**RID** Not regulated

**ADR** Not regulated

**ADN** Not regulated

**15. REGULATORY INFORMATION**

**International Inventories**

TSCA Complies  
 DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

**SARA 311/312 Hazard Categories**

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

**CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Silica Sand	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Silica Sand	X	X	X	X	
Portland Cement	X	X	X		

**International Regulations**

**Mexico**

**National occupational exposure limits**

Component	Carcinogen Status	Exposure Limits
Respirable Crystalline Silica ( 15 - 40 )		Mexico: TWA= 0.1 mg/m <sup>3</sup>
Portland Cement ( 10 - 30 )		Mexico: TWA 10 mg/m <sup>3</sup> Mexico: STEL 20 mg/m <sup>3</sup>

*Mexico - Occupational Exposure Limits - Carcinogens*

**Canada**

**WHMIS Hazard Class**

Not determined

**16. OTHER INFORMATION**

<b>NFPA</b>	<b>Health Hazards</b> 2	<b>Flammability</b> 0	<b>Instability</b> 0	<b>Physical and Chemical Hazards</b> -
<b>HMIS</b>	<b>Health Hazards</b> 2	<b>Flammability</b> 0	<b>Physical Hazard</b> 0	<b>Personal Protection</b> X

**Prepared By** Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

**Revision Date** 10-Nov-2015

**Revision Note** No information available

**User's Responsibility** The OSHA Hazard Communication Standard 29 CFR 1910.1200 requires that this SDS be made available to your employees who handle or may be exposed to this product. Educate and train your employees regarding applicable precautions. Instruct your employees to handle this product properly.

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**